

SELECTOR GRABS

Selector Grabs are a popular tool for loading and sorting a wide variety of materials for recycling and an efficient tool when demolishing structures.



- 360° rotation allows optimal positioning and precise handling, and the solid perforated shells provide excellent visibility for operators.
- Their versatility allows them access to the demolition, construction, waste and forestry sectors.
- Weight range 1.5 – 50T.

Applications:

- Construction Site Handling: Precisely sort and move construction materials, such as rocks, timber, and scrap, improving site organization and efficiency.
- Demolition Debris Sorting: Efficiently separate and handle demolition debris for easier disposal and recycling, reducing cleanup time.
- Waste Recycling: Accurately pick and sort recyclable materials from mixed waste streams, enhancing recycling operations and material recovery rates.
- Perfect for light demolition.

DEMOLITION AND SELECTOR GRABS SPECIFICATIONS

Model	Unit	SG80	SG150	SG300	SG350	SG1000	SG1500	SG2500	SG4000	SG4500	SG5000
Excavator Weight	T	0.7-1.2	1.2-3	4-7	6-10	10-15	14-22	22-26	24-30	28-37	30-50
Weight	KG	80	160	310	465	810	1055	1415	1500	1825	2685
Cylinder	BAR	200	200	200	300	350	350	350	350	350	350
	L/PM	15	25	35	70	80	160	170	170	200	200
360° Rotation	BAR	100	100	100	100	160	160	160	160	160	160
	L/MIN	5	10	10	15	20	25	30	30	30	35
	TR/MIN	10	10/15	10/14	10/15	10/15	10/15	10/15	10/15	10/15	10/15
Force	N	6000	15000	20000	25000	30000	35000	50000	50000	80000	90000
Width (Open Shells)	MM	600	750	1150	1550	1750	1950	2100	2100	2250	2250
Height	MM	595	700	770	990	1200	1300	1400	1400	1550	1650
Internal Height	MM	190	280	320	380	450	520	630	630	550	650
Volume	L	30	70	100	200	400	500	800	850	950	1100